

Lydisolering

Facader - Døre - Vinduer



12.2012



WICONA[®]
TECHNOLOGY FOR IDEAS

Lydisolering

	<i>Desibel, dB</i>		<i>Fylkning</i>	
	<i>Rw</i>	<i>(C, Crt)</i>		
Vinduer				
WICLINE 65 evo	39	(-2;-4)	Consafis Plus Phon 32/40	
	39	(-2;-5)	Consafis Plus Phon 32/40	
	43	(-2;-5)	Consafis Plus Phon 32/43	
	45	(-1;-4)	Consafis Plus Phon 45/51	
	45	(-1;-5)	Consafis Plus Phon 32/47	
	45	(-2;-4)	Consafis Plus Phon 42/47	
	47	(-1;-4)	Consafis Plus Phon 45/51	
	47	(-1;-4)	Consafis Plus Phon 45/51	
WICLINE 75 evo	<i>Se WICLINE 65 evo</i>			
WICLINE 125	42	(-2;-7)	<i>Udvendig Fylkning</i>	<i>Indvendig fylkning</i>
	44	(-2;-5)	24 Thermoplus SN	24 Thermoplus SN
	44	(-1;-5)	6 K-glas	24 Thermoplus SN
	46	(-1;-4)	6 K-glas	24 Thermoplus SN
	47	(-1;-4)	6 K-glas	30 Thermoplus SN
	47	(-1;-4)	6 K-glas	36 Phonstop TH SN
	47	(-2;-4)	30 Thermoplus SN	30 Thermoplus SN
	47	(-2;-6)	6 K-glas	30 Thermoplus SN
	48	(-2;-5)	6 K-glas	36 Thermoplus SN
Døre				
WICSTYLE 65 evo	39	(-2;-5)	Consafis Plus Phon 32/40	
	43	(-1;-4)	Consafis Plus Phon 45/51	
	43	(-2;-6)	Consafis Plus Phon 42/47	
	43	(-2;-6)	Sanco Phon PS 50/40	
WICSTYLE 75 evo	<i>Se WICSTYLE 65 evo</i>			
Skydedøre				
WICSLIDE 160	37	(-1;-4)	Climaplus Ultra N WS 30/40	
	39	(-1;-4)	Climaplus Ultra N Silence	
	40	(-1;-3)	Climaplus Ultra N Silence WS 49/52	
	40	(-1;-4)	Climaplus Ultra N Silence WS 38/46	
	41	(-2;-5)	Climatop Ultra N Silence WS 44/47	
Facader				
WICTEC 50	38	(-2;-4)	Sanco Phon SP VE 40/32 III	
	38	(-2;-4)	Sanco Phon SP VE 40/32 III	
	43	(-2;-4)	Sanco Phon SC SP VN 45/37 III	
	43	(-2;-4)	Sanco Phon SP VN 50/42 III	
	47	(-1;-4)	Sanco Phon SC SP VN 50/42 III	
	47	(-1;-4)	Sanco Phon SP VN 50/42 III	
	50		Phonstop 46/54 GH	
WICTEC 60	47	(-2;-5)	Phonstop TH 42/54 GH	
	48	(-1;-4)	Iplus R Icaphone S 56/50-1.7	