








































































| Serie | Abbildung Figure | Artikel-Nr. Article-No. | Bestell.-Nr. Order-No. | Artikelbezeichnung Article designation | Kennzeichen Mark |
|----------------|-------------------------------------------------------------------------------------|----------------------------|---------------------------|------------------------------------------------------------------------------------------------------|---------------------|
| WICTEC 50 |  | 112283 | W0112283.00 | Bauanschlussprofil 50/86,6 mm Profile for junction to structure 50/86.6 mm | ! |
| universell |  | 123943 | W0123943.00 | Glasleiste 3,5/20 mm Glazing bead 3.5/20 mm | ! |
| universell |  | 130809 | W0130809.03 | Eckwinkel-Vormaterial 58,2/118,2 mm Corner angle pre-material 58.2/118.2 mm | ! |
| WICTEC 50 |  | 135031 | W0135031.00 | Riegelprofil E3, 50/45,5 mm Transom profile E3, 50/45.5 mm | ! |
| WICTEC 50 |  | 135043 | W0135043.00 | Riegelprofil Traufe E3, 75/65,5 mm Eaves transom E3, 75/65.5 mm | ! |
| WICTEC 50 |  | 135111 | W0135111.00 | Andruckprofil einseitig 33,3 mm Pressure profile, one-sided, 33.3 mm | ! |
| WICTEC 50 |  | 135112 | W0135112.00 | Andruckprofil einseitig 36,9/5 mm Pressure profile, one-sided, 36.9/5 mm | ! |
| WICTEC 50 |  | 135123 | W0135123.00 | Andruckprofil 10°-26°, 46,8/5 mm Pressure profile 10°-26°, 46.8/5 mm | ! |
| WICTEC 50 |  | 135124 | W0135124.00 | Andruckprofil 26°-37°, 46,8/5 mm Pressure profile 26°-37°, 46.8/5 mm | ! |
| WICTEC 50 |  | 135216 | W0135216.00 | Wetterschenkel Glasanb. 43/ 10,6 mm Weather bar profile for glazed annexes, 43/10.6 mm | ! |
| WICTEC 50 |  | 135249 | W0135249.00 | Riegelprofil Industriekontur E2, 50/145,5 mm Transom E2, Industr. façade, 50/145.5 mm | ! |
| WICTEC 50 |  | 135274 | W0135274.00 | Andruckprofil integriert 40/14 mm Pressure profile integrated, 40/14 mm | ! |
| WICTEC 50 |  | 169238 | W0169238.00 | Traufrinnenbefestigungsprofil 78/20 mm Eaves gutter fixing profile, 78/20 mm | ! |
| WICTEC 50 |  | 169249 | W0169249.00 | Andruckprofil 72/16,2 mm Pressure profile, 72/16.2 mm | ! |
| WICLINE 75 evo |  | 1010452 | W01010452.01 | Kämpfer/Sprosse Industriekontur 23/73/104,8 mm Transom/Glaz. bar Industrial design 23/73/104.8 mm | ! |

| Serie | Abbildung Figure | Artikel-Nr. Article-No. | Bestell.-Nr. Order-No. | Artikelbezeichnung Article designation | Kennzeichen Mark |
|-----------------|-------------------------------------------------------------------------------------|----------------------------|---------------------------|-----------------------------------------------------------------------------------------------------------------|---------------------|
| WICLINE 75 evo |  | 1010453 | W1010453.01 | Flügelprofil Überschlag Ind.-Des. 48/25,5/85 mm <i>Overlapping leaf/sash pr. ind. des. 48/25.5/85 mm</i> | ! |
| WICLINE 65 evo |  | 1010599 | W1010599.01 | Aufsatzprofil Plattenmontage v. außen 57/32/65 mm <i>Supplem. pr. panel assemb. from outs. 57/32/65 mm</i> | ! |
| WICLINE 65 evo |  | 1010600 | W1010600.01 | Flügelprofil auswärts 23,1/80/75 mm <i>Leaf/Sash profile, outwards, 23.1/80/75 mm</i> | ! |
| WICSTYLE 75 evo |  | 1020461 | W1020461.01 | Türflügelprofil einwärts Überschlag 94/83/91 mm <i>Door leaf profile, inwards, overlap 94/83/91 mm</i> | ! |
| WICSTYLE 77 FP |  | 1020463 | W1020463.125 | Sockelprofil FP 83/108/77 mm <i>Bottom rail profile FP, 83/108/77 mm</i> | ! |
| WICSTYLE 75 evo |  | 1020502 | W1020502.01 | Spezialblendrahmen Klassik-Design Tür 46/82/95 mm <i>Special frame pr., classic design door 46/82/95 mm</i> | ! |
| WICSTYLE 75 evo |  | 1020508 | W1020508.125 | Sockelprofil 102/127/74,8 mm <i>Bottom rail profile, 102/127/74.8 mm</i> | ! |
| WICSTYLE 75 evo |  | 1020510 | W1020510.01 | Türflügelpr. einw. Üb. Klassik-Design 94/83/88 mm <i>Door leaf pr. inw. overl. classic des. 94/83/88 mm</i> | ! |
| WICSTYLE 77 FP |  | 1021233 | W1021233.125 | Sockelaufsatz einw./ausw. 13,5/27,5/91,8 mm <i>Bottom rail suppl.prof.inw./outw.13.5/27.5/91.8 mm</i> | ! |
| WICSLIDE 65 |  | 1041239 | W1041239.01 | Kupplungsprofil 26/26/68,9 mm <i>Coupling profile, 26/26/68.9 mm</i> | ! |
| WICSLIDE 65 |  | 1041271 | W1041271.01 | Flügelprofil Schiebe ni verstärkt 68/68/67 mm <i>Leaf/Sash pr., sliding, reinf. inw., 68/68/67 mm</i> | ! |
| WICLINE 65 evo |  | 1916092 | W1916092.01 | Einspannblendrahmen SK 55,5/46/75/FD = 26 mm <i>Clamping frame, SK 55.5/46/75/inf.thickn. = 26 mm</i> | ! |
| WICLINE 65 evo |  | 1916124 | W1916124.01 | Stulpflügel-Spezialprofil verd. 27/76/75/F = 56 mm <i>Double c.spec.pr.f.conc.sash,27/76/75/rebate=56 mm</i> | ! |
| WICLINE 65 evo |  | 1916248 | W1916248.01 | Stütze na verstärkt 30/80/140 mm <i>Mullion, externally reinforced, 30/80/140 mm</i> | ! |
| WICLINE 65 evo |  | 1916304 | W1916304.01 | Schwellenprofil wärmed. ausw. 66,5/14 mm <i>Thermally insulated thresh. pr., outw., 66.5/14 mm</i> | ! |

| Serie | Abbildung Figure | Artikel-Nr. Article-No. | Bestell.-Nr. Order-No. | Artikelbezeichnung Article designation | Kennzeichen Mark |
|-----------------|-------------------------------------------------------------------------------------|----------------------------|---------------------------|-------------------------------------------------------------------------------------------------------|---------------------|
| WICLINE 65 evo |  | 1916338 | W1916338.01 | Sprosse Klassik-Design 14/50/64,5 mm Glaz. bar profile, classic design, 14/50/64.5 mm | ! |
| WICLINE 75 evo |  | 1917122 | W1917122.01 | Stulpflügel-Spezialprofil Klassik 19/73/94,5 mm Double c. sash special pr., classic, 19/73/94.5 mm | ! |
| WICSTYLE 65 |  | 1926527 | W1926527.125 | Falzverbreiterung 79/79/64,8 mm Rebate widening profile 79/79/64.8 mm | ! |
| WICSTYLE 75 evo |  | 1927532 | W1927532.01 | Unterbauprofil Kämpfer Türseitenteil 74,6/34 mm Substruct.pr., transom, lat. part door, 74.6/34 mm | ! |
| WICLINE 65N |  | 3000005 | W3000005.03 | Eckwinkel-Vormaterial 33,2/84,2 mm Corner angle pre-material 33.2/84.2 mm | ! |
| WICLINE 75 evo |  | 3000230 | W3000230.03 | Eckwinkel-Vormaterial 23,2/74,2 mm Corner angle pre-material 23.2/74.2 mm | ! |
| WICTEC 50 |  | 3030060 | W3030060.00 | Abdeckprofil Sonnenschutz, beidseitig 50/123 mm Cover for sunshade, rails on both sides, 50/123 mm | ! |
| WICTEC 50 |  | 3030061 | W3030061.00 | Abdeckprofil Sonnenschutz, einseitig 50/123 mm Cover for sunshade, rail on one side, 50/123 mm | ! |
| WICTEC 50 |  | 3030085 | W3030085.00 | Glasleiste 21/25,5 mm für Eloxaloberflächen Glazing bead 21/25.5 mm for anodized surfaces | ! |
| WICSLIDE 160 |  | 3041329 | W3041329.01 | Zusatzprofil 28,9/26 mm Additional profile 28.9/26 mm | ! |
| WICSTYLE 65 |  | 3090032 | W3090032.01 | Zusatzprofil Mittigverglasung 2,5/25 mm Additional profile for centre glazing 2.5/25 mm | ! |
| WICSTYLE 65 |  | 3090034 | W3090034.01 | Zusatzprofil Mittigverglasung 4,3/29 mm Additional profile centre glazing 4.3/29mm | ! |
| WICSTYLE 77 FP |  | 3090074 | W3090074.00 | Glasleiste 45/22 mm Glazing bead 45/22 mm | ! |
| WICLINE 115 AFS |  | 3090090 | W3090090.01 | Glasleiste 17/41 mm Glazing bead 17/41 mm | ! |
| WICSTYLE 77 FP |  | 3090240 | W3090240.01 | Glasleiste 12/22 mm Glazing bead 12/22 mm | ! |

| Serie | Abbildung Figure | Artikel-Nr. Article-No. | Bestell.-Nr. Order-No. | Artikelbezeichnung Article designation | Kennzeichen Mark |
|-----------------|-------------------------------------------------------------------------------------|----------------------------|---------------------------|-------------------------------------------------------------------------------------------------------------|---------------------|
| WICLINE 75 evo |  | 3090259 | W3090259.01 | Glasleiste Industrie-Design 12/18 mm <i>Glazing bead industrial design 12/18 mm</i> | ! |
| WICLINE 75 evo |  | 3090262 | W3090262.01 | Glasleiste Industrie-Design 29/18 mm <i>Glazing bead industrial design 29/18 mm</i> | ! |
| WICLINE 65 evo |  | 3090268 | W3090268.01 | Bauanschlussprofil 195,1/50,5 mm <i>Profile for junction to structure 195.1/50.5 mm</i> | ! |
| WICLINE 65 evo |  | 3090269 | W3090269.01 | Zusatzprofil 21,6/17,9 mm, bearbeitet <i>Additional profile, 21.6/17.9 mm, machined</i> | ! |
| WICSTYLE 75 evo |  | 3091001 | W3091001.00 | Glasleiste 4/18 mm <i>Glazing bead 4/18 mm</i> | ! |
| WICLINE 65 |  | 3091006 | W3091006.00 | Glasleiste 23/18 mm <i>Glazing bead 23/18 mm</i> | ! |
| WICLINE 65 |  | 3091038 | W3091038.00 | Kupplungsprofil 25/17,9 mm <i>Coupling profile, 25/17.9 mm</i> | ! |
| universell |  | 3091054 | W3091054.00 | Verstärkungsprofil Fenstertür 21/43 mm <i>Reinforcement profile for French window, 21/43 mm</i> | ! |
| WICSTYLE 75 evo |  | 3900044 | W3900044.03 | Eckwinkel-Vormaterial 63,9/114,9 mm <i>Corner angle pre-material 63.9/114.9 mm</i> | ! |
| WICSTYLE 75 evo |  | 3925096 | W3925096.01 | Aufsatzprofil für Türflügel auswärts 13,5/25 mm <i>Supplem. profile for door leaf, outw., 13.5/25 mm</i> | ! |
| universell |  | 3991266 | W3991266.01 | Glasleiste für Nassverglasung 12/22 mm <i>Glazing bead for wet glazing 12/22 mm</i> | ! |
| universell |  | 3991275 | W3991275.01 | Glasleiste für Nassverglasung 37/22 mm <i>Glazing bead for wet glazing 37/22 mm</i> | ! |
| universell |  | 3991276 | W3991276.01 | Glasleiste für Nassverglasung 41/22 mm <i>Glazing bead for wet glazing 41/22 mm</i> | ! |
| universell |  | 3991277 | W3991277.01 | Glasleiste für Nassverglasung 45/22 mm <i>Glazing bead for wet glazing 45/22 mm</i> | ! |
| universell |  | 3991279 | W3991279.01 | Glasleiste für Nassverglasung 52/22 mm <i>Glazing bead for wet glazing 52/22 mm</i> | ! |

| Serie | Abbildung Figure | Artikel-Nr. Article-No. | Bestell.-Nr. Order-No. | Artikelbezeichnung Article designation | Kennzeichen Mark |
|-----------------|-------------------------------------------------------------------------------------|----------------------------|---------------------------|--------------------------------------------------------------------------------------------------------------|---------------------|
| WICSTYLE 75 evo |  | 4050632 | W4050632 | Gusseckwinkel Alu, Kammer 52,7 mm <i>Cast aluminium corner angle, chamber 52.7 mm</i> | ! |
| WICTEC 50EL |  | 4080002 | W4080002 | Vorklotz, Alu <i>Glazing support, aluminium</i> | ! |
| WICTEC 50 |  | 4080187 | W4080187 | Konsole, integrierter Sonnenschutz <i>Bracket for integrated sunshade</i> | ! |
| WICTEC EL60 |  | 4080208 | W4080208 | Montageteil, Alu <i>Mounting part, aluminium</i> | ! |
| WICSTYLE 65 evo |  | 4390010 | W4390010 | Dämmstoffeinschub 26 x 66 mm <i>Insulating material insertion 26 x 66 mm</i> | ! |
| WICSTYLE 77 FP |  | 6010118 | W6010118.1970 | Aluminium-Rollenband WICONA 3-tlg. ein-/auswärts <i>Aluminium butt hinge WICONA, 3 pieces, inw./outw.</i> | ! |
| WICSTYLE 75 evo |  | 6023131 | W6023131 | MV Autotronic 834P 2-flg Fkt B 45 PZ 2118 R <i>M. lock autotr. 834P 2 leaf func. B 45 PZ 2118 R</i> | ! |
| WICSTYLE 75 evo |  | 6023408 | W6023408 | Mehrfachverr. 833PK Fkt. E DM 35 PZ 2348 DIN R+L <i>Multi. lock 833PK fun.E DM 35 PZ 2348 DIN R+L</i> | ! |
| WICSTYLE 75 evo |  | 6081397 | W6081397 | Stößelkontakt MFV 834/881 f. Türband verd., 4 m <i>Tappet contact MFV 834/881 f. door h. concea., 4 m</i> | ! |
| WICSTYLE 75 evo |  | 6920106 | W6920106 | Fallen-Riegelschloss Fkt. B Verr. o. DM 35 R/RZ <i>Latch bolt l., func. B lock. tow. top DM 35 R/RZ</i> | ! |
| WICLINE 65 evo |  | 6950103 | W6950103.1836 | Wendelager aufliegend mit Sperre WL 65 R+L <i>Vert. axis pivot top mount. with detent WL65 R+L</i> | ! |